

P19202.P01

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

P19202

Total Pages

Inventor(s) or Application Identifier

Akira ATSUTA

Title: MODEM APPARATUS, COMMUNICATION CONTROL
APPARATUS, COMMUNICATION TERMINAL APPARATUS
AND COMMUNICATION CONTROL METHOD

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231**APPLICATION ELEMENTS****ACCOMPANYING APPLICATION PARTS**

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 44]
(preferred arrangement set forth below)
- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total Sheets 8]
4. ☒ Oath or Declaration [Total Pages 3]
a. ☒ Newly executed (original or copy) ☐ Unexecuted
b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 18 completed)
[Note Box 5 below]
i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s)
named in the prior application, see 37 CFR 1.63(d)(2)
and 1.33(b).
- ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy
of the oath or declaration is supplied under Box 4b, is considered
as being part of the disclosure of the accompanying application
and is hereby incorporated by reference therein.
- ☐ Microfiche Computer Program (Appendix)
- Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement verifying identity of above copies

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure ☐ Copies of IDS Citations
Statement (IDS)/PTO-1449
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
15. ☐ The prior application is assigned of record to _____
16. ☒ Foreign priority claimed
a. ☒ Claim of Priority
b. ☒ Certified Copy of Priority Document(s)
17. ☐ Other: _____

18. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior Application No. _____/_____, filed _____.19. ☐ Amend the specification by inserting before the first line the sentence:

This application is a ___ continuation-in-part, ___ continuation, ___ division, of Application No. _____/_____, filed _____.

Address all future correspondence to **Customer No. 7055** at the present address of:**GREENBLUM & BERNSTEIN, P.L.C.**
1941 Roland Clarke Place
Reston, VA 20191
(703) 716-1191

Date

Signature

Bruce H. Bernstein, Reg. No. 29,027
Typed or Printed Name

SPECIFICATION

Title of the Invention :

MODEM APPARATUS,
COMMUNICATION CONTROL APPARATUS,
COMMUNICATION TERMINAL APPARATUS
AND COMMUNICATION CONTROL METHOD

Inventor :

Akira ATSUTA

MODEM APPARATUS, COMMUNICATION CONTROL APPARATUS,
COMMUNICATION TERMINAL APPARATUS
AND COMMUNICATION CONTROL METHOD

5 BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a modem apparatus,
10 communication control apparatus and communication
terminal apparatus with the function of performing
communications based on the communication procedure
conforming to a predetermined Recommendation of ITU-T
Recommendations and the communication control method
15 therefor.

Description of the Related Art

A communication terminal apparatus provided with
20 a modem for performing communications based on the
communication procedure conforming to the predetermined
Recommendation of ITU-T Recommendations has
conventionally performed communications based on the
communication procedure conforming to the predetermined
25 Recommendation as an answering terminal by exchanging
procedure signals, which are expected in the
communication procedure, with a calling terminal.

For example, as illustrated in FIG.1A, the communication terminal apparatus provided with a modem for performing communications based on the communication procedure conforming to ITU-T Recommendation V.32 (hereinafter referred to as "Recommendation V.32") as an answering terminal transmits an ANS signal to a calling terminal in response to a call placed from the calling terminal. The calling terminal transmits an AA signal to the answering terminal after detecting the ANS signal.

10 The answering terminal transmits an AC signal to the calling terminal after detecting the AA signal. Further, as illustrated in FIG.1B, the communication terminal apparatus provided with the modem for performing communications based on the communication procedure conforming to Recommendation V.32 as the answering terminal transmits the ANS signal to the calling terminal in response to the received signal, and when a predetermined time passes after transmitting the ANS signal, further transmits the AC signal to the calling terminal.

20 The calling terminal transmits the AA signal to the answering terminal after detecting the AC signal. Thus, the calling and answering terminals mutually transmit and receive expected procedure signals, thereby performing communications based on the communication procedure conforming to Recommendation V.32.

25

However, in the conventional communication terminal apparatus, when the procedure signals are

transmitted and received according to a sequence specified in the predetermined Recommendation, the case sometimes occurs that the procedure signal transmitted from the answering terminal is not correctly identified at the calling terminal. Thereby, the calling terminal cannot transmit the procedure signal expected by the answering terminal, resulting in the problem that the communication causes the looped condition thereof.

In the above-mentioned example, for example, in the case illustrated in FIG.1C, when the answering terminal transmits the ANS signal to the calling terminal, the case sometimes occurs that the calling terminal does not recognize the ANS signal correctly, and transmits the CM signal specified in Recommendation V.8 to the answering terminal. In this case, the answering terminal continues to transmit the AC signal to the calling terminal because the AA signal expected from the AC signal is not transmitted from the calling terminal. Meanwhile, the calling terminal continues to transmit the CM signal to the answering terminal because a JM signal expected from the CM signal is not transmitted from the answering terminal. Thereby, the communication causes the looped condition thereof.

Such a problem occurs similarly in the communication terminal apparatus provided with a modem for performing communications based on the communication procedure conforming to Recommendation T.30. Namely, as

illustrated in FIG.2A, the answering terminal continues to transmit a DIS signal to the calling terminal after transmitting the DIS signal because a DCS signal expected from the DIS signal is not transmitted from the calling terminal. Meanwhile, the calling terminal also continues to transmit the CM signal to the answering terminal because the JM signal expected from the CM signal is not transmitted from the answering terminal. Further, also in the case illustrated in FIG.2B, the answering terminal continues to transmit the DIS signal after transmitting the DIS signal because the DCS signal expected from the DIS signal is not transmitted from the calling terminal. Meanwhile, the calling terminal continues to transmit the AA signal because the AC signal expected from the AA signal is not transmitted from the answering terminal. Thus, the communication causes the looped condition thereof.

SUMMARY OF THE INVENTION

20 An object of the present invention is to provide a modem apparatus, communication control apparatus, communication terminal apparatus and communication control method capable of responding to the communication procedure specified in an arbitrary Recommendation and assuredly preventing the apparatus from causing the looped condition thereof.

To solve the above-mentioned problem, the apparatus

and method of the present invention detect a procedure signal transmitted from a calling terminal while or after a transmission section, which transmits procedure signals specified in the predetermined Recommendation, transmits a DIS signal specified in Recommendation T.30 or a procedure signal used in data communication, from signals received in a reception section, then in the case where the procedure signal is a CM signal specified in Recommendation V.8, shifts the operation to the communication operation conforming to Recommendation V.8, and in the case where the procedure signal is that used in the data communication, shifts the operation to the data communication operation.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects and features of the invention will appear more fully hereinafter from a consideration of the following description taken in connection with the accompanying drawing wherein one example is illustrated by way of example, in which;

FIG.1A is a sequence diagram in conventional communication terminal apparatuses;

FIG.1B is a sequence diagram in conventional communication terminal apparatuses;

FIG.1C is a sequence diagram in conventional communication terminal apparatuses;

FIG.2A is another sequence diagram in the

conventional communication terminal apparatuses;

FIG.2B is another sequence diagram in the conventional communication terminal apparatuses;

FIG.3 is a hardware block diagram of a communication terminal apparatus according to an embodiment of the present invention;

FIG.4 is a block diagram of a communication control unit of the communication terminal apparatus according to one embodiment of the present invention;

FIG.5 is a diagram illustrating carrier frequencies at which signal components are calculable in a variable signal detection section in the communication control unit of the communication terminal apparatus according to the above embodiment;

FIG.6 is a flowchart to explain operations in the case where the communication control unit of the communication terminal apparatus of the above embodiment performs a FAX preferential communication;

FIG.7 is a flowchart to explain operations in the case where the communication control unit of the communication terminal apparatus of the above embodiment performs a data preferential communication;

FIG.8A is a sequence diagram in the case where the communication control unit of the communication terminal apparatus of the above embodiment receives various signals after transmitting a DIS signal; and

FIG.8B is a sequence diagram in the case where the

communication control unit of the communication terminal apparatus of the above embodiment receives various signals after transmitting a DIS signal; and

FIG.8C is a sequence diagram in the case where the communication control unit of the communication terminal apparatus of the above embodiment receives various signals after transmitting a DIS signal; and

FIG.9 is a sequence diagram in the case where the communication control unit of the communication terminal apparatus of the above embodiment receives a CM signal after transmitting an AC signal.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

One embodiment of the present invention is explained specifically below with reference to accompanying drawings.

FIG.3 is a hardware block diagram of the communication terminal apparatus 1 according to the above embodiment. Specific examples of the communication terminal apparatus 1 are, for example, a facsimile apparatus, a personal computer or a multi-function apparatus which has a facsimile function, copy function and printer function and so on.

CPU (Central Processing Unit) 11 controls operations of each composition of the communication terminal apparatus 1 by executing various programs

stored in ROM 12. RAM 13 is a main-memory, Which is used by CPU 11 in executing the program read from ROM 12 and date.

Scanner I/F 15, printer I/F 16, keyboard 17,
5 external I/O 18 are connected with CPU 11 via bus 14. CPU 11 controls operations of them by executing program stored in ROM 12.

Scanner I/F 15 is an interface connectable to scanner 19. CPU11 controls the operation of scanner 19
10 via scanner I/F 15. Scanner 19 scans image data of documents according to control of CPU 11.

Printer I/F 16 is an interface connectable to printer 20. CPU11 controls the operation of printer 20 via Printer I/F 16. Printer 20 prints out, for example
15 image data received with modem, which is described later, according to control of CPU 11.

Keyboard 17 is for use in receiving instructions from operator of the communication terminal apparatus. The operator operates the communication terminal
20 apparatus by inputting predetermined instructions.

External I/O 18 communicates data with external apparatuses 21, such as a speaker and microphone which input/output data of predetermined speech signals and so on. External I/O 18 is, for example, a serial
25 interface including USB (Universal Serial Bus).

Moreover modem 101 and communication control section 113 are connected with CPU 11 via bus 14. CPU

11 controls operations of them by executing program
stored in ROM 12.

Modem 101 controls transmission/reception of data
and signals between public switched telephone networks
5 (PSTN). Modem 101 is provided with a variable signal
detection section, which is capable of calculating an
integrated value of a signal component at a specific
carrier frequency. This variable signal detection
section is described later.

10 Communication control section 113 works as a host
of modem 101 (hereinafter, Communication control section
is referred to as host). Host 113 controls data
communication and facsimile communication via the PSTN,
by controlling modem 101.

15 Host 113 is provided with a detection frequency
table that is used in setting frequency detectable by
the variable signal detection section of modem 101. Host
113 is further provided with a communication capability
table that is used in setting communication capabilities
20 of the communication terminal apparatus 1. Host 113 is
provided with the detection frequency table and
communication capability table according to one
embodiment of the present invention, however it may be
possible to provide RAM 13 with these tables.

25 FIG.4 is a block diagram of a communication control
unit 100 comprised with the above-mentioned modem 101
and host 113. In this embodiment, this communication

control unit 100 has the function of performing communications based on the communication procedure conforming to Recommendation V.8.

In FIG.4, modem 101 is comprised of DSP (Digital
5 Signal Processor) and controls operations of, for example, internal signals by itself. Modem 101 is connected to a PSTN (Public Switched Telephone Networks) through AFE (Analog Front End) 102. AFE 102 is connected to reception section 103 that receives, for example,
10 signals from the PSTN and transmission section 104 that transmits, for example, signals to the PSTN. Reception section 103 is connected to variable signal detection section 105, detection section 106 that detects a signal of 2100 Hz (hereinafter referred to as "2100 Hz detection
15 section") and V.8 signal detection section 107. Transmission section 104 is connected to V.8 signal detection section 107.

Variable signal detection section 105 has a plurality of band pass filters each capable of
20 calculating an integrated value of a signal component at a specific carrier frequency. Host 113 sets the integrated value of the signal component at the specific carrier frequency to be calculated at each of the band pass filters. Hereinafter, in the case where host 113
25 sets an integrated value of a signal component at a carrier frequency of a high channel in Recommendation V.21 (hereinafter referred to as "Recommendation V.21

(H) ") at one of the band pass filters , the band pass filter is referred to as V21(H) detection section 108. Variable signal detection section 105 calculates the integrated value of the signal components at carrier frequency set
 5 by host 113 as described above. FIG.4 illustrates the case where host 113 sets other band pass filters as V.22 detection section 109, V.22bis detection section 110, V.32 detection section 111, and V.32bis detection section 112 besides V.21(H) detection section 108.

10 FIG.5 illustrates specific carrier frequencies at which signal components are calculable in variable signal detection 105 that is set as illustrated in FIG.4.

V.21(H) detection section 108 calculates the integrated value of the signal component at a carrier
 15 frequency band of 1650Hz to 1850Hz used in Recommendation V.21(H). Specifically, V.21(H) detection section 108 calculates the integrated value of the signal component at the carrier frequency of the DCS signal that is transmitted from a calling terminal to an answering
 20 terminal in Recommendation T.30, as the signal energy.

V.22 detection section 109 and V.22bis detection section 110 each calculates an integrated value of a signal component at a carrier frequency band of 900Hz to 1500Hz used in Recommendation V.22 and Recommendation
 25 V.22bis. Specifically, V.22 detection section 109 and V.22bis detection section 110 each calculates the integrated values of the signal components at the carrier

frequency band of the S1 signal and SB1 signal that are transmitted from a calling terminal to an answering terminal in Recommendation V.22 and Recommendation V22bis, as the respective signal energy. In addition, Recommendation V.22 and Recommendation V.22bis are both Recommendations for use in performing data communications. The S1 signal and SB1 signal are the procedure signals transmitted from the calling terminal to the answering terminal in the case where data communications are performed.

V.32 detection section 111 and V.32bis detection section 112 each calculates an integrated value of a signal component at a carrier frequency of 1800 Hz used in Recommendation V.32 and Recommendation V.32bis. Specifically, V.32 detection section 111 and V.32bis detection section 112 each calculates the integrated value of the signal component at the carrier frequency of the AA signal that is transmitted from a calling to an answering terminal in Recommendation V.32 and Recommendation V32bis, as the signal energy. In addition, Recommendation V.32 and Recommendation V.32bis are both Recommendations for use in performing data communications. The AA signal is the procedure signal transmitted from the calling terminal to the answering terminal in the case where data communications are performed.

Variable signal detection section 105 is not

limited in the integrated values of signal components at carrier frequencies as described above, and can calculate integrated values of signal components at carrier frequencies used in other Recommendations, such as, for example, the integrated value of the signal component at the carrier frequency used in Recommendation V.23, and the integrated value of the signal component at the carrier frequency used in Recommendation V.26bis.

2100Hz detection section 106 is used in the case where communication terminal apparatus 1 functions as a calling terminal, and calculates an integrated value of a signal component of a carrier frequency of 2100 Hz. Specifically, 2100Hz detection section 106 calculates the integrated value of the signal component at the carrier frequency of, for example, the ANSam signal that is transmitted from an answering terminal to a calling terminal in Recommendation V.8 or the CED signal that is transmitted from an answering terminal to a calling terminal in Recommendation T.30, as the respective signal energy.

V.8 signal detection section 107 analyzes a received signal received in reception section 103. V.8 signal detection section 107 detects the JM signal when the received signal is the JM signal, further detects the CM signal when the received signal is the CM signal, and furthermore detects the CJ signal when the received

signal is the CJ signal. In addition, V.8 signal detection section 107 receives the CM signal and CJ signal as received signals when communication terminal apparatus 1 functions as an answering terminal. On the other hand, V.8 signal detection section 107 receives the JM signal as the received signal when communication terminal apparatus 1 functions as a calling terminal. When V.8 signal detection section 107 detects the JM signal, CM signal or CJ signal, the section 107 notifies host 113 of the reception of the respective signal.

Detection sections 108 to 112 set in variable signal detection section 105 and 2100Hz detection section 106 are each connected to maximum-value detection section 114. Maximum-value detection section 114 detects a maximum value from among integrated values of signal components at carrier frequencies calculated in detection sections 108 to 112 and 2100Hz detection section 106. Specifically, maximum-value detection section 114 compares the respective integrated values of signal components at carrier frequencies calculated in detection sections 108 to 112 set in variable signal detection section 105 and 2100Hz detection section 106 to each other to detect the maximum value of the integrated value of the signal component at the carrier frequency. In addition, maximum-value detection section 114 is connected to comparison section 115.

Comparison section 115 has predetermined

thresholds registered thereto for each integrated value of the signal component at the carrier frequency. Comparison section 115 compares the maximum value detected in maximum-value detection section 114 to the registered threshold. When the maximum value exceeds the predetermined threshold, comparison section 115 detects an identification signal indicative of the detection section that calculates the maximum value, and based on the identification signal, notifies host 113 of a type of the received signal.

Host 113 is provided with control section 116 that controls the whole operations of communication control unit 100. Host 113 is further provided with DIS determination section 117 that determines whether or not the received signal notified from modem 101 is the DIS signal, DCS determination section 118 that determines whether or not the received signal notified from modem 101 is the DCS signal, and memory 121 in which detection frequency table 119 and communication capability table 120 are stored. In addition, DIS determination section 117 is used when communication terminal apparatus 1 functions as a calling terminal, and DCS determination section 118 is used when communication terminal apparatus 1 functions as an answering.

Detection frequency table 119 is a table for use by control section 116 in setting a band pass filter of variable signal detection section 105 in modem 101.

Communication capability table 120 is a table for use by control section 116 in setting the CM signal that notifies the answering terminal of communication capabilities of communication control unit 100.

5 Operations of communication control unit 100 with the above-mentioned configuration are next explained for two cases; the case that communication control unit 100 performs communications preferentially according to the communication procedure conforming to Recommendation
10 T.30 (hereinafter referred to as "FAX preferential communication"), and the case that communication control unit 100 performs communications according to the communication procedure conforming to Recommendation V.22/22bis and Recommendation V.32/32bis and so on
15 (hereinafter referred to as "data preferential communication"). FIG.6 illustrates a flowchart in the case where communication control unit 100 performs the FAX preferential communication. FIG.7 illustrates a flowchart in the case where communication control unit
20 100 performs the data preferential communication. The flow in the case where communication control unit 100 performs the FAX preferential communication is first explained. In addition, it is assumed that communication terminal apparatus 1 is an answering
25 terminal.

First, communication control unit 100 answers a call placed from a calling terminal.

When communication control unit 100 answers the call, or receives a predetermined instruction from an operator while calling in the telephone mode (ST301), modem 101 of communication control unit 100 transmits
5 based on the instruction from host 113 the CED signal specified in Recommendation T.30 or the ANsam signal specified in Recommendation V.8 to the calling terminal (ST302).

After transmitting the CED signal or ANsam signal,
10 communication control unit 100 determines whether or not the CM signal specified in Recommendation V.8 is received from the calling terminal (ST303). Specifically, V.8 signal detection section 107 of modem 101 analyzes the received signal received from the calling terminal, and
15 notifies host 113 of the analyzed result. Host 113 determines whether or not the CM signal is received when receives the notification.

At this point, in the case where the CM signal is received from the calling terminal, since communication
20 control unit 100 has the function for performing communications based on the communication procedure conforming to Recommendation V.8, communication control unit 100 performs communications based on the communication procedure conforming to Recommendation
25 V.8.

Namely, in the case where the CM signal is received from the calling terminal, based on the instruction from

host 113, transmission section 104 of modem 101 transmits the JM signal to the calling terminal (ST304).

After transmitting the JM signal, communication control unit 100 determines whether or not the CJ signal specified in Recommendation V.8 is received from the calling terminal (ST305). Specifically, V.8 signal detection section 107 of modem 101 analyzes the signal received from the calling terminal, and notifies host 113 of the analyzed result. Host 113 determines whether or not the CJ signal is received when receives the notification.

At this point, in the case where the CJ signal is received from the calling terminal, transmission section 104 of modem 101 discontinues the transmission of the JM signal (ST306). Then, based on the instruction from host 113, modem 101 shifts to the next processing (ST307). Accordingly, modem 101 finishes the communication procedure based on Recommendation V.8. Then, modem 101 performs a communication based on a communication procedure which is recognized during the communication procedure of Recommendation V.8 and is the most appropriate for a communication with the calling terminal. The communication procedure which is recognized during the communication procedure of Recommendation V.8 and is the most appropriate for the communication with the calling terminal includes communication procedures conforming to, for example,

Recommendation V.34, Recommendation V.90,
Recommendation V.91 and Recommendation V.92.

In addition, in the case where a predetermined time
passes while the CJ signal is not received, based on the
5 instruction from host 113, modem 101 discontinues the
communication channel, or returns to the telephone mode
(ST308).

On the other hand, in the case where the CM signal
is not received from the calling terminal, communication
10 control unit 100 determines whether or not an automode
signal (i.e. AA signal defined in Recommendation V.32bis)
is received from the calling terminal (ST309). In
addition, the automode signal includes, for example, the
S1 signal and SB1 signal specified in Recommendation
15 V.22/V.22bis, and AA signal specified in Recommendation
V.32/V.32bis.

Specifically, variable signal detection section
105 of modem 101 calculates the integrated value of the
signal component at the carrier frequency of the received
20 signal. Then, variable signal detection section 105
outputs the calculated integrated values to
maximum-value detection section 114. Maximum-value
detection section 114 detects the maximum value of the
integrated value. Maximum-value detection section 114
25 outputs the maximum value to comparison section 115.
Comparison section 115 compares the maximum value to the
registered threshold. Then, when the maximum-value

exceeds the predetermined threshold, comparison section 115 detects an identification signal indicative of the detection section that calculates the maximum value, and based on the identification signal, notifies host 113 of the type of the received signal. After receiving the notification, host 113 determines whether or not the automode signal is received.

At this point, in the case where the signal is received, it is determined whether or not communication control unit 100 has the communication capabilities corresponding to the received automode signal. When communication control unit 100 has the communication capabilities corresponding to the received automode signal, communication control unit 100 performs communications based on the communication procedure corresponding to the automode signal.

Specifically, in communication control unit 100, host 113 determines whether or not the apparatus 100 has the communication capabilities corresponding to the automode signal (ST310). When communication control unit 100 has the communication capabilities corresponding to the automode signal, host 113 determines whether or not an operator desires to perform communications with the communication capabilities (ST311). When the operator desires to perform communications with the communication capabilities, based on the instruction from host 113, modem 101 performs

communications based on the communication procedure corresponding to the received automode signal (ST312).

For example, when the automode signal received from the calling terminal is the AA signal, the integrated values calculated by V.32 detection section 111 and V.32bis detection section 112 in variable signal detection section 105 indicate the maximum value in the processing performed by maximum-value detection section 114, and exceeds the registered threshold value in the processing performed by comparison section 115. Comparison section 115 detects identification signals indicative of V.32 detection section 111 and V.32bis detection section 112, and based on the identification signals, notifies host 113 that the received signal is the AA signal. When host 113 receives the notification, host 113 determines whether or not communication control unit 100 has the communication capabilities corresponding to Recommendation V.32 or V.32bis. When communication control unit 100 has the communication capabilities corresponding to Recommendation V.32 or V.32bis, it is determined whether or not an operator desires to perform communications with the communication capabilities. When the operator desires to perform communications with the communication capabilities, based on the instruction from host 113, modem 101 performs communications based on the communication procedure corresponding to Recommendation V.32 or V.32bis.

In addition, in the case where communication control unit 100 does not have the communication capabilities corresponding to the automode signal, or in the case where the operator does not desire to perform communications with the communication capabilities corresponding to the automode signal, based on the instruction from host 113, modem 101 discontinues the communication channel, or returns to the telephone mode (ST320).

On the other hand, when the automode signal is not received, in communication control unit 100, host 113 determines whether or not a predetermined time passes after initiating the transmission of the CED signal or ANSam signal at ST302 (ST313).

At this point, when the predetermined time passes after initiating the transmission of the CED signal or ANSam signal, since communication control unit 100 is set to perform the FAX preferential communication, based on the instruction from host 113, transmission section 104 of modem 101 transmits the DIS signal specified in Recommendation T.30 to the calling terminal (ST314). Thereafter, communication control unit 100 shifts to a FAX communication mode. In addition, when the predetermined time does not pass after initiating the transmission of the CED signal or ANSam signal, host 113 repeats the processing of ST303 to ST313.

After transmitting the DIS signal to the calling

terminal, communication control unit 100 determines whether or not the CM signal is received from the calling terminal (ST315). In communication terminal apparatus 1, after transmitting the DIS signal, and shifting to the FAX communication mode, variable signal detection section 105 still monitors the signal component at the carrier frequency of the received signal, which is different from the conventional communication terminal apparatus that cannot receive any signal except the DCS signal specified in Recommendation T.30 which is an expected signal when the DIS signal is transmitted. Accordingly, communication terminal apparatus 1 can concurrently detect the procedure signal specified in Recommendation T.30 and the other procedure signals specified in Recommendations other than Recommendation T.30. It is thus possible for communication terminal apparatus 1 to recognize the procedure signal transmitted from the calling terminal, and consequently to prevent the communication from causing the looped condition.

At this point, when the CM signal is received from the calling terminal, since communication control unit 100 has the function for performing communications based on the communication procedure conforming to Recommendation V.8, communication control unit 100 performs communications based on the communication procedure conforming to Recommendation V.8. In addition,

in this case, communication control unit 100 executes the same processing as in ST304 to ST308.

On the other hand, when the CM signal is not received from the calling terminal, communication control unit 100 determines whether or not the DCS signal specified in Recommendation T.30 is received from the calling terminal (ST316). In addition, when the determination on the DCS signal is performed, communication control unit 100 executes the same processing as in the case where the determination on the automode signal is performed.

At this point, when the DCS signal is received, since communication control unit 100 is set to perform the FAX preferential communication, communication control unit 100 performs communications based on the communication procedure conforming to Recommendation T.30 (ST317).

On the other hand, when the DCS signal is not received, communication control unit 100 determines whether or not the automode signal is received from the calling terminal (ST318). In addition, in this case, communication control unit 100 executes the same processing in ST309.

At this point, when the automode signal is received from the calling terminal, it is determined whether or not communication control unit 100 has the communication capabilities corresponding to the received automode signal. Then, when communication control unit 100 has

the communication capabilities corresponding to the received automode signal, communication control unit 100 performs communications based on the communication procedure corresponding to the automode signal. In addition, in this case, communication control apparatus 100 executes the same processing as in ST310 to ST312.

On the other hand, when the automode is not received from the calling terminal, host 113 determines whether or not a predetermined time passes after initiating the transmission of the DIS signal at ST314 (ST319).

At this point, when the predetermined time passes after initiating the transmission of the DIS signal, based on the instruction from host 113, modem 101 discontinues the communication channel, or returns to the telephone mode (ST320). In addition, when the predetermined time does not pass after initiating the transmission of the DIS signal, host 113 repeats the processing of ST315 to ST319.

FIG.8 illustrates a sequence diagram in the case where various signals are received after transmitting the DIS signal at ST314 in the above-mentioned flow.

FIG.8A illustrates the case that the CM signal is received at ST315, and the communication is performed based on the communication procedure conforming to Recommendation V.8. As illustrated in FIG.8A, in the case where the calling terminal transmits the CM signal after communication control unit 100 transmits the DIS

signal to the calling terminal, transmitting the JM signal in response to the CM signal prevents the communication from causing the looped condition.

FIG.8B illustrates the case that the AA signal is received at ST318, the communication is performed based on the commination procedure conforming to Recommendation V.32/V.32bis. In the same way as receiving the CM signal at ST315, transmitting the AC signal in response to the AA signal prevents the communication from causing the looped condition.

FIG.8C illustrates the case that communication control unit 100 does not have the communication capabilities corresponding to the AA signal at ST310, or that the operator dose not desire to perform communications with the communication capabilities corresponding to the AA signal at ST311. In the former case, since communication control unit 100 does not have the communication capabilities corresponding to the AA signal, discontinuing the communication channel prevents the communication from causing the looped condition.

Thus, communication control unit 100 performs the FAX preferential communication. In this case, even when communication control unit 100 transmits the DIS signal without receiving the predetermined signal from the calling terminal after transmitting the CED signal or ANSam signal, variable signal detection section 105

monitors the signal component at the carrier frequency of the received signal. Accordingly, communication control unit 100 can detect the CM signal or automode signal while transmitting the DIS signal. It is thereby possible for communication terminal apparatus 1 to shift to the next processing based on the CM signal or automode signal. As a result, it is possible to prevent the communication in the communication terminal apparatus 1 from causing the looped condition.

10 The flow in the case where communication terminal apparatus 1 performs the data preferential communication is next explained.

First, communication control unit 100 answers a call placed from a calling terminal.

15 When communication control unit 100 answers the call, or receives a predetermined instruction from an operator while calling in the telephone mode (ST501), modem 101 of communication control unit 100 transmits based on the instruction from host 113 the ANS signal specified, for example, in Recommendation V.32 or the ANsam signal specified in Recommendation V.8 to the calling terminal (ST502).

After transmitting the ANS signal or ANsam signal, communication control unit 100 determines whether or not the CM signal specified in Recommendation V.8 is received from the calling terminal (ST503). Specifically, V.8 signal detection section 107 of modem 101 analyzes the

received signal from the calling terminal, and notifies host 113 of the analyzed result. Host 113 determines whether or not the CM signal is received when receives the notification.

5 At this point, when the CM signal is received from the calling terminal, since communication control unit 100 has the function for performing communications based on the communication procedure conforming to Recommendation V.8, communication control unit 100
10 performs communications based on the communication procedure conforming to Recommendation V.8. In addition, in the case where the communication is performed based on the communication procedure conforming to Recommendation V.8, communication control unit 100
15 executes the operations of ST304 to ST308 in the same way as performing the FAX preferential communication.

On the other hand, when the CM signal is not received from the calling terminal, communication control unit 100 determines whether or not the automode signal is
20 received from the calling terminal (ST504). In addition, in the case where communication control unit 100 determines whether or not the automode signal is received, or executes the processing of the case where the outmode signal is received, communication control unit 100
25 performs the operations of ST310 to ST312 in the same way as performing the FAX preferential communication.

In addition, when communication control unit 100

does not have the communication capabilities corresponding to the automode signal, or the operator does not desire to perform communications with the communication capabilities corresponding to automode
5 signal, communication control unit 100 discontinues the communication channel, or returns to the telephone mode, based on the instruction from host 113, in the same way as in the case where communication control unit 100 performs the FAX preferential communication (ST320).

10 When the automode signal is not received, in communication control unit 100, host 113 determines whether or not a predetermined time passes after initiating the transmission of the ANS signal or ANSam signal at ST502 (ST505).

15 At this point, when the predetermined time passes after initiating the transmission of the ANS signal or ANSam signal, since communication control unit 100 is set to perform the data preferential communication, based on the instruction from host 113, transmission
20 section 104 of modem 101 transmits the AC signal specified in, for example, Recommendation V.32 to the calling terminal (ST506). Thereafter, communication control unit 100 shifts to a data communication mode. In addition, when the predetermined time does not pass after
25 initiating the transmission of the ANS signal or ANSam signal, host 113 repeats the processing of ST503 to ST505.

After transmitting the AC signal to the calling

terminal, communication terminal apparatus 1 determines whether or not the CM signal is received from the calling terminal (ST507). In communication control unit 100, after transmitting the AC signal, and shifting to the data communication mode, variable signal detection section 105 still monitors the signal component at the carrier frequency of the received signal, which is different from the conventional communication terminal apparatus that cannot receive any signal except the AA signal specified in, for example, Recommendation V.32 which is an expected signal when the AC signal is transmitted. Accordingly, communication terminal apparatus 1 can concurrently detect the procedure signal specified in, for example, Recommendation V.32 and the other procedure signals specified in Recommendations other than the corresponding Recommendation. It is thus possible for communication terminal apparatus 1 to recognize the procedure signal transmitted from the calling terminal, and consequently to prevent the communication from causing the looped condition.

At this point, when the CM signal is received from the calling terminal, since communication control unit 100 has the function for performing communications based on the communication procedure conforming to Recommendation V.8, communication control unit 100 performs the communication based on the communication procedure conforming to Recommendation V.8. In addition,

in this case, communication control unit 100 executes the same processing as at ST304 to ST308.

On the other hand, when the CM signal is not received from the calling terminal, communication control unit
5 100 determines whether or not the automode signal is received from the calling terminal (ST508). In addition, in this case, communication control unit 100 executes the same processing as at ST504.

At this point, when the automode signal is received
10 from the calling terminal, it is determined whether or not communication control unit 100 has the communication capabilities corresponding to the received automode signal. Then, when communication control unit 100 has the communication capabilities corresponding to the
15 received automode signal, communication control unit 100 performs the communication based on the communication procedure corresponding to the automode signal. In addition, in this case, communication control unit 100 executes the same processing as at ST310 to ST312.

20 On the other hand, when the automode is not received from the calling terminal, host 113 determines whether or not a predetermined time passes after initiating the transmission of the AC signal at ST506 (ST509).

At this point, when the predetermined time passes
25 after initiating the transmission of the AC signal, based on the instruction from host 113, modem 101 discontinues the communication channel, or returns to the telephone

mode (ST320). In addition, when the predetermined time does not pass after initiating the transmission of the AC signal, host 113 repeats the processing of ST507 to ST509.

5 FIG.9 illustrates a sequence diagram in the case where the CM signal is received from the calling terminal after transmitting the AC signal at ST506 in the above-mentioned flow. FIG.9 illustrates the case that the CM signal is received at ST507, and then the
10 communication is performed based on the communication procedure conforming to V.8 Recommendation. As illustrated in FIG.9, even in the case where the calling terminal transmits the CM signal after communication control unit 100 transmits the AC signal to the calling
15 terminal, transmitting the JM signal in response to the CM signal prevents the communication from causing the looped condition.

Thus, communication control unit 100 performs the data preferential communication. In this case, even
20 when communication control unit 100 transmits the AC signal without receiving the predetermined signal from the calling terminal after transmitting the ANS signal or ANSam signal, variable signal detection section 105 monitors the signal component at the carrier frequency
25 of the received signal. Accordingly, communication control unit 100 can detect the CM signal while transmitting the AC signal. It is thereby possible for

communication terminal apparatus 1 to shift to the next processing based on the received CM signal. As a result, it is possible to prevent the communication in the communication control apparatus 100 from causing the
5 looped condition.

Thus, according to communication terminal apparatus 1 of this embodiment, after transmitting the DIS signal to the calling terminal in the case where the FAX preferential communication is performed, by
10 detecting the signal component at the carrier frequency of the procedure signal conforming to an arbitrary type of Recommendation transmitted from a calling terminal, it is possible to shift to the next processing based on the procedure signal. As a result, it is possible to
15 prevent the communication in communication terminal apparatus 1 from causing the looped condition.

Further, according to communication terminal apparatus 1 of this embodiment, after transmitting, for example, the AC signal to the calling terminal in the
20 case where the data preferential communication is performed, by detecting the signal component at the carrier frequency of the procedure signal conforming to an arbitrary type of Recommendation transmitted from a calling terminal, it is possible to shift to the next
25 processing based on the procedure signal. As a result, it is possible to prevent the communication in communication terminal apparatus 1 from causing the

looped condition.

Furthermore, according to communication terminal apparatus 1 of this embodiment, by setting variable signal detection section 105 of modem 101, it is possible to limit the reception of the procedure signal conforming to an arbitrary type of Recommendation received from the calling terminal. It is thereby possible for a user to designate the type of Recommendation that the user desires to communicate. For example, in the case where communication terminal apparatus 1 receives the procedure signal specified in the type of Recommendation which communication terminal apparatus 1 cannot respond is received, the setting to immediately discontinue the communication channel with the calling terminal can reduce the communication time with the calling terminal with which communication terminal apparatus 1 cannot communicate and therefore further reduce the communication cost.

In addition, this embodiment describes communication terminal apparatus 1 with the function for performing communications based on the communication procedure conforming to Recommendation V.8. However, this embodiment is not limited to such apparatuses with the function for performing communications based on the communication procedure conforming to Recommendation V.8. For example, this embodiment is applicable to, for example, a communication terminal apparatus with the

function for performing communications based on the communication procedures conforming to Recommendation V.30 and Recommendation V.32, in other words, communication terminal apparatus with the function for performing both FAX communication and data communication. By applying this embodiment to such apparatus, in the case where the apparatus receives the AA signal from the calling terminal after transmitting the DIS signal in the FAX communication mode, it is possible to shift to the next processing based on the AA signal. As a result, it is possible to prevent the communication in the communication terminal apparatus from causing the looped condition.

As described above, according to the present invention, the procedure signal conforming to an arbitrary Recommendation transmitted from the calling terminal is detected after the procedure signal specified in the predetermined Recommendation, thereby it is possible to respond to the communication procedure conforming to the arbitrary Recommendation, and consequently assuredly prevent the apparatus itself from causing the looped condition.

The present invention is not limited to the above described embodiments, and various variations and modifications may be possible without departing from the scope of the present invention.

This application is based on the Japanese Patent

Application No. HEI11-257399 filed on September 10, 1999,
entire content of which is expressly incorporated by
reference herein.

Application No. HEI11-257399 filed on September 10, 1999,
entire content of which is expressly incorporated by
reference herein.

What is claimed is:

1. A modem at an answering side that performs a transmission and reception of a signal with another modem at a calling side through a communication channel,
5 comprising:

a transmission section that is configured to transmit a procedure signal specified in a predetermined ITU-T Recommendation;

10 a reception section that is configured to receive the signal transmitted from said another modem at the calling side;

a detection section that is configured to detect another procedure signal transmitted from said another modem at the calling side while or after said transmission
15 section transmits a DIS signal specified in Recommendation T.30 from signals received in said reception section; and

an identification section that is configured to output an identification signal indicative of a type of
20 Recommendation that said another modem at the calling side uses to a host, based on a detected result in said detection section,

wherein said modem shifts to an operation mode corresponding to an instruction of said host based on
25 said identification signal.

2. The modem according to claim 1, wherein when the procedure signal detected in said detection section is

a CM signal specified in Recommendation V.8, based on said instruction of said host, said modem shifts to a communication procedure specified in a Recommendation that is appropriate for a communication with said another
5 modem at the calling side, while when the procedure signal detected in said detection section is a procedure signal used in a data communication, based on said instruction of said host, said modem shifts to a data communication operation.

10 3. A modem at an answering side that performs a transmission and reception of a signal with another modem at a calling side through a communication channel, comprising:

a transmission section that is configured to
15 transmit a procedure signal specified in a predetermined ITU-T Recommendation;

a reception section that is configured to receive the signal transmitted from said another modem at the calling side;

20 a detection section that is configured to detect another procedure signal transmitted from said another modem at the calling side while or after said transmission section transmits the procedure signal used in a data communication from signals received in said reception
25 section; and

an identification section that is configured to output an identification signal indicative of a type of

Recommendation that said another modem at the calling side uses to a host, based on a detected result in said detection section,

wherein said modem shifts to an operation mode
5 corresponding to an instruction of said host based on said identification signal.

4. The modem according to claim 3, wherein when the procedure signal detected in said detection section is a CM signal specified in Recommendation V.8, based on
10 said instruction of said host, the modem shifts to a communication procedure specified in a Recommendation that is appropriate for a communication with said another modem at the calling side.

5. A modem at an answering side that performs a
15 transmission and reception of a signal with another modem at a calling side through a communication channel, comprising:

a transmission section that is configured to transmit a procedure signal specified in a predetermined
20 ITU-T Recommendation;

a reception section that is configured to receive the signal transmitted from said another modem at the calling side;

a detection section that is configured to detect
25 another procedure signal transmitted from said another modem at the calling side while or after said transmission section transmits a DIS signal specified in

Recommendation T.30 or a procedure signal used in a data communication from signals received in said reception section; and

an identification section that is configured to
5 output an identification signal indicative of a type of Recommendation that said another modem at the calling side uses to a host, based on a detected result in said detection section,

wherein said modem shifts to an operation mode
10 corresponding to an instruction of said host based on said identification signal.

6. The modem according to claim 5, wherein when the procedure signal detected in said detection section is a CM signal specified in Recommendation V.8, based on
15 said instruction of said host, the modem shifts to a communication procedure specified in a Recommendation that is appropriate for a communication with said another modem at the calling side, while when the procedure signal detected in said detection section is a procedure signal
20 used in the data communication, based on said instruction of said host, the modem shifts to a data communication operation.

7. The modem according to claim 5, wherein according to said instruction of said host based on said
25 identification signal, the modem shifts to an operation mode to continue a communication conforming to a Recommendation corresponding to said identification

signal, to discontinue said communication channel, or to return to a telephone mode.

8. The modem according to claim 5, wherein said detection section detects respective signals at a plurality of frequencies including a procedure signal expected from the procedure signal of which transmission is currently continued or finished and a procedure signal except an expected procedure signal.

9. A communication control apparatus provided with a modem at an answering side that performs a transmission and reception of a signal with another modem at a calling side through a communication channel, and a host which controls said modem, said modem comprising:

a transmission section that is configured to transmit a procedure signal specified in a predetermined ITU-T Recommendation;

a reception section that is configured to receive the signal transmitted from said another modem at the calling side;

a detection section that is configured to detect another procedure signal transmitted from said another modem at the calling side while or after said transmission section transmits a DIS signal specified in Recommendation T.30 or a procedure signal used in a data communication from signals received in said reception section; and

an identification section that is configured to

output an identification signal indicative of a type of Recommendation that said another modem at the calling side uses to a host, based on a detected result in said detection section,

5 said host comprising:

a control section that is configured to instruct said transmission section to transmit a procedure signal conforming to said predetermined ITU-T Recommendation, while switching an operation mode of said modem
10 corresponding to the identification signal output from said identification section of said modem.

10. The communication control apparatus according to claim 9, said control section of said host shifts a communication procedure of said mode to a communication
15 procedure specified in a Recommendation that is appropriate for a communication with said another modem at the calling side when the procedure signal detected in said detection section is a CM signal specified in Recommendation V.8, and shifts the communication
20 procedure of said modem to a data communication operation when the procedure signal detected in said detection section is a procedure signal used in the data communication.

11. A communication terminal apparatus at an answering
25 terminal that performs a transmission and reception of a signal and data with another communication terminal apparatus at a calling side through a communication

channel, comprising:

the communication control apparatus according to claim 9;

a recording unit that is configured to record image
5 data received from said another communication terminal apparatus at the calling side through said communication channel; and

a scanning unit that is configured to scan image data to be transmitted to said another communication
10 terminal apparatus at the calling side through said communication channel.

12. A method for controlling a communication with a modem at a calling side through a communication channel, comprising:

15 receiving a signal transmitted from said modem at the calling side while or after transmitting a DIS signal conforming to ITU-T Recommendation T.30 or a procedure signal used in a data communication;

detecting another procedure signal conforming to
20 a predetermined ITU-T Recommendation from signals received from said mode at the calling side; and

shifting to a communication operation conforming to Recommendation V.8 when a detected procedure signal is a CM signal specified in Recommendation V.8, while
25 shifting to a data communication operation when the detected procedure signal is a procedure signal used in the data communication.

ABSTRACT OF THE DISCLOSURE

A communication control apparatus of the present invention detects a procedure signal transmitted from a calling side from signals received in reception section while or after a transmission section, which transmits procedure signals specified in the predetermined Recommendation, transmits a DIS signal specified in Recommendation T.30 or a procedure signal used in a data communication. Then, the apparatus shifts to a communication operation conforming to Recommendation V.8 when the detected procedure signal is a CM signal specified in Recommendation V.8, while shifting to a data communication operation when the detected signal is the procedure signal used in the data communication. Thus, the present invention enables the apparatus to shift to the communication operation corresponding to the detected procedure signal, and therefore it is possible to assuredly prevent the apparatus from causing the looped condition thereof.




FIG.1A




FIG.1B




FIG.1C




FIG.2A




FIG.2B




FIG.3

FIG. 4 is a block diagram of a communication system.




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8A




FIG.8B




FIG.8C




FIG.9

Declaration and Power of Attorney For Utility or Design Patent Application
特許出願宣言書

Japanese Language Declaration

私は、下欄に氏名を記載した発明者として、以下のとおり
宣言する:
私の住所、郵便の宛先および国籍は、下欄に氏名に続いて記載したとおり
であり、
名称の発明に関し、請求の範囲に記載した特許を求める主題の本来の、
最初にして唯一の発明者である(一人の氏名のみが下欄に記載されている
場合)か、もしくは本来の、最初にして共同の発明者である(複数の氏名が
下欄に記載されている場合)と信じ、

As a below named inventor, I hereby declare that:
My residence, post office address and citizenship are as stated
below next to my name.
I believe I am the original, first and sole inventor (if only one name
is listed below) or an original, first and joint inventor (if plural
names are listed below) of the subject matter which is claimed
and for which a patent is sought on the invention entitled

MODEM APPARATUS, COMMUNICATION CONTROL
APPARATUS, COMMUNICATION TERMINAL APPARATUS
AND COMMUNICATION CONTROL METHOD

記発明の明細書(下記の欄でX印がついていない場合は、
添書に添付)は、
年 月 日に提出され、
米国出願番号
とし、
(該当する場合) 年 月 日に訂正されました。又は、
特許協定条約国際出願番号
とし、
(該当する場合) 年 月 日に訂正されました。

the specification of which is attached hereto unless the following
box is checked:
was filed on as
United States Application Number
and was amended on (if applicable) or,
PCT International Application Number
and was amended on (if applicable)

私は、前期のとおり補正した請求の範囲を含む前記明細書の内容を検
査し、理解したことを陳述する。
私は、連邦規則法典第37編第1条第56項定義されるとおり、特許資格
の有無について重要な情報を開示すべき義務をあることを認めます。
私は合衆国法典第35部第119条(a-d)項又は第365条(b)項に基づく、
下記の外国特許出願又は発明者証出願、或いは第365条(a)項に基づく、
少なくとも米国以外の1ヶ国を指名したPCT国際出願の外国優先権を主張
し、更に優先権の主張に係わる基礎出願の出願日前の出願日を有する外国
特許出願、又は発明者証出願或いはPCT国際出願を以下に"なし"の箱に
印をつけることにより明記する:

I hereby state that I have reviewed and understand the contents of
the above identified specification, including the claims, as
amended by any amendment referred to above.
I acknowledge the duty to disclose information which is material to
patentability as defined in Title 37, Code of Federal Regulations,
§1.56.
I hereby claim foreign priority under Title 35, United States Code
§119(a-d) or §365(b) of any foreign application(s) for patent or
inventor's certificate, or §365(a) of any PCT international
application which designated at least one country other than the
United States, listed below. I have also identified below, by
checking the "No" box, any foreign application for patent or
inventor's certificate, or of any PCT international application having
a filing date before that of the application on which priority is
claimed:

Table with 4 columns: Prior foreign applications, Country, Filing Date, and Priority claimed. It lists foreign applications with their numbers, countries, and filing dates, and allows the applicant to claim or not claim priority for each.

その他の外国特許出願番号は別紙の追補優先権欄にて記載する。
Additional foreign application numbers are listed on a
supplemental priority sheet attached hereto.

Japanese Language Utility or Design Patent Application Declaration

私は、合衆国法典第35部第119条(e)項に基づき、下記の合衆国仮特許出願の利益を主張する。

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

(Application Number)
(番号)

(Day/Month/Year Filed)
出願の年月日

(Application Number)
(番号)

(Day/Month/Year Filed)
出願の年月日

(Application Number)
(番号)

(Day/Month/Year Filed)
出願の年月日

□ その他の合衆国仮特許出願番号は別紙の追補優先権欄にて記載する。

□ Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

私は、合衆国法典第35部第120条に基づき下記の合衆国特許出願、又は第365条(c)項に基づき合衆国を指名したPCT国際出願の利益を主張し、本願の請求の範囲各項に記載の主題が合衆国法典第35部第112条第1項規定の態様で、先の合衆国特許出願又はPCT国際出願に開示されていない限りにおいて、先の出願の出願日と本願の国内出願日又はPCT国際出願日の間に有効となった連邦規則法典第37部第1章第56条に記載の特許要件に所要の情報を開示すべき義務を有することを認める。

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

(Application No.)
(出願番号)

(Day/Month/Year Filed)
(出願の年月日)

(現況) (Status)
(特許済み、係属中、放棄済み) (patented, pending, abandoned)

(Application No.)
(出願番号)

(Day/Month/Year Filed)
(出願の年月日)

(現況) (Status)
(特許済み、係属中、放棄済み) (patented, pending, abandoned)

□ その他の合衆国又は国際特許出願番号は別紙の追補優先権欄にて記載する。

□ Additional U. S. or international application numbers are listed on a supplemental priority sheet attached hereto.

私は、ここに自己の知識にもとづいて行った陳述がすべて真実であり、自己の有する情報および信ずるところに従って行った陳述が真実であると信じ、さらに故意に虚偽の陳述等を行った場合、合衆国法典第18部第1001条により、罰金もしくは禁錮に処せられるか、またはこれらの刑が併科され、またかかる故意による虚偽による陳述が本願ないし本願に対して付与される特許の有効性を損なうことがあることを認識して、以下の陳述を行ったことを宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

私、下記署名者は、ここに記載の米国弁護士または代理人に本出願に関し特許商標庁にて取られるいかなる行為に関して、同米国弁護士又は代理人が、私に直接連絡なしに私の外国弁護士或るいは法人代表者からの指示を受け取り、それに従うようここに委任する。この指示を出す者が変更の場合には、ここに記載の米国弁護士又は代理人にその旨通知される。

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from either his foreign patent agent or corporate representative, if any, as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

Japanese Language Utility or Design Patent Application Declaration

委任状： 私は、下記発明者として、下記に明記された顧客番号を伴う以下の弁護士又は、代理人をここに選任し、本順の手続きを遂行すること並びにこれに関する一切の行為の特許商標庁に対して行うことを委任する。そして全ての通信はこの顧客番号宛に発送される。

顧客番号 7055

現在選任された弁護士は下記の通りである。

Neil F. Greenblum
Bruce H. Bernstein
James L. Rowland
Arnold Turk

POWER OF ATTORNEY: As a named inventor, I hereby appoint the attorney(s) and/or agent(s) associated with the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number:

CUSTOMER NUMBER 7055

The appointed attorneys presently include:

Reg. No. 28,394
Reg. No. 29,027
Reg. No. 32,674
Reg. No. 33,094

Address: **GREENBLUM & BERNSTEIN, P.L.C.**
1941 ROLAND CLARKE PLACE
RESTON, VA 20191

直接電話連絡先 : (名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

GREENBLUM & BERNSTEIN, P.L.C.
(703)716-1191

唯一のまたは第一の発明者の氏名	Full name of sole or first inventor Akira ATSUTA
同発明者の署名 日付	Inventor's signature Date <i>Akira Atsuta</i> 2000.3.3
住所	Residence 4-30-4-201, Fujimidai, Nerima-ku, Tokyo 177-0034 Japan
国籍	Citizenship Japan
郵便の宛先	Post Office Address 4-30-4-201, Fujimidai, Nerima-ku, Tokyo 177-0034 Japan
第2の共同発明者の氏名 (該当する場合)	Full name of second joint inventor, if any
同第2共同発明者の署名 日付	Second Inventor's signature Date
住所	Residence
国籍	Citizenship
郵便の宛先	Post Office Address

(第三またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)